



# Technical Data Sheet

# Ravasol PVA-30-P

## *Emulsion Polymer*

## Description

Ravasol PVA-30-P is a plasticized aqueous Polyvinyl Acetate homopolymer stabilized with Polyvinyl Alcohol.

## Applications

Ravasol PVA-30-P is a multipurpose contractor grade primer/sealer/bonding liquid and can be used on substrates such as plaster, cement, timber, gypsum wall boards and paper. Ravasol PVA-30-P can be added to cement to increase strength and can also be diluted with water, to allow easy addition and application. Typical applications are:-

- Bonding liquid and sealer
- Base for ceramic tile adhesives
- Base for building adhesives

## Properties

Property	Specification
Solids Content	29 – 31%
pH	4 – 6
Viscosity (Brookfield 3/20)	9000 – 12000 mPas
Minimum Film Forming Temperature	Less than 5 deg C

## Packaging

- Intermediate Bulk Containers (IBC)
- Can also be supplied in bulk truck

## Shelf Life

When stored / un-opened in the original packaging and protected from direct sun light at 5-25°C the shelf life exceeds 6 months. If customer's storage conditions are not aligned to these parameters, then tests should be carried out to determine the shelf life under alternative and specific storage conditions.



*The data in this Technical Data Sheet is provided for information only. It is correct to the best of our knowledge, information and belief at the date of its publication. It does not constitute a specification and no liability is assumed, nor freedom from any existing patents.*

*Ravasol is a trademark owned by Ravago Chemicals.*

*Ravago Chemicals Ltd | Unit 1 Fordham House | Newmarket Road | Ely | CB7 5LL | United Kingdom | Tel +44 1638 724 912*