



Technical Data Sheet

Ravasol PVA-Dex

Emulsion Polymer

Description

Ravasol PVA-Dex is an aqueous Polyvinyl Acetate homopolymer stabilized with Dextrin.

Applications

Ravasol PVA-Dex is a raw material for the adhesives industry. The high solids content / low viscosity enables high speed running characteristics and enables formulation adhesives with fast drying speed and clean film appearance. Typical adhesive applications are:-

- Re-moistenable adhesives (envelope flap type)
- Tube winding adhesives
- Book binding adhesives
- Paper / card box and carton manufacture

Properties

Property	Specification
Solids Content	63 – 67%
pH	4 – 6
Viscosity (Brookfield 3/20)	500 – 1500 mPas
Minimum Film Forming Temperature	~13 deg C

Packaging

- 1000 litre Intermediate Bulk Containers at 1200 kg nett
- Can also be supplied in bulk truck

Shelf Life

When stored / un-opened in the original packaging and protected from direct sun light at 5-25°C the shelf life exceeds 6 months. If customer's storage conditions are not aligned to these parameters, then tests should be carried out to determine the shelf life under alternative and specific storage conditions.



The data in this Technical Data Sheet is provided for information only. It is correct to the best of our knowledge, information and belief at the date of its publication. It does not constitute a specification and no liability is assumed, nor freedom from any existing patents.

Ravasol is a trademark owned by Ravago Chemicals.

Ravago Chemicals Ltd | Unit 1 Fordham House | Newmarket Road | Ely | CB7 5LL | United Kingdom | Tel +44 1638 724 912