



Technical Data Sheet

Ravasol SA-2

Emulsion Polymer

Description

Ravasol SA-2 is an aqueous polymer emulsion based on Styrene and Acrylic Acid Esters, stabilized with APEO-free surfactants.

Applications

Ravasol SA-2 is highly compatible and stable with cement and mortar. The low Tg provides high elasticity without the need for additional plasticizers or coalescing solvents. Typical applications are:-

- Cement and mortar modifications
- Highly flexible tile adhesives
- Fillers, slurries and basecoats
- Surface patching compounds
- Water-proof and flexible roof membranes

Properties

Property	Specification
Solids Content	58 – 60%
pH	6 – 9
Viscosity (Brookfield 3/20)	300 – 1000 mPas
Minimum Film Forming Temperature	0 deg C
Glass Transition Temperature	-10 deg C

Packaging

- Intermediate Bulk Containers (IBC)
- Can also be supplied in bulk truck

Shelf Life

When stored / un-opened in the original packaging and protected from direct sun light at 5-25°C the shelf life exceeds 6 months. If customer's storage conditions are not aligned to these parameters, then tests should be carried out to determine the shelf life under alternative and specific storage conditions.



The data in this Technical Data Sheet is provided for information only. It is correct to the best of our knowledge, information and belief at the date of its publication. It does not constitute a specification and no liability is assumed, nor freedom from any existing patents.

Ravasol is a trademark owned by Ravago Chemicals.

Ravago Chemicals Ltd | Unit 1 Fordham House | Newmarket Road | Ely | CB7 5LL | United Kingdom | Tel +44 1638 724 912